MaxiCut Ultra 44-4745D cut-resistant gloves

Cut-resistant-knitted gloves

Item number: 100-50-001



PPE CATEGORY II

NBR forms the contact surface when picking up and guiding workpieces.

Material	**polyamide, steel fibre, Polyester, ultra-high molecular weight polyethylene (UHMWPE), elastane, glass fibre Coating: nitrile butadiene rubber (NBR)**
Colour	
Sizes	**6, 7, 8, 9, 10, 11, 12**
Country of origin	**Sri Lanka**
Sales unit	**Pair**
Brand	**ATG®**

Performance levels to EN 388

Abrasion resistance	●●●●	4 of 4
Cut resistance (Coupe)		X - no rated level
Tear resistance	●●●●	4 of 4
Puncture resistance	●●●○	3 of 4
Cut resistance (TDM)		D

EN ISO 21420:2020+A1:2024	General requirements for protective gloves
EN 388:2016+A1:2018	Mechanical risks · 4X43D
EN 16350:2014	Electrostatic properties of protective gloves · Rv < 1,0 × 10^8 Ω
Marking	ANSI/ISEA 105:2016 · A4
OEKO-TEX STANDARD 100	
Marking	Skin Health Alliance (dermatological accreditation)

Product overview based on manufacturer documents. Refer also to the original instructions and EU declaration of conformity.

ATG MaxiCut Ultra 44-4745D cut-resistant gloves

Protection and standards

Marking	Food contact: Regulation (EC) 1935/2004; dry, non-fatty foods only; short-term contact up to 30 minutes at 40 °C

Care

40 °C with standard detergent; 3 wash cycles; Air dry

Product overview based on manufacturer documents. Refer also to the original instructions and EU declaration of conformity.