Article 2210 - Winter Gloves LATEX - PPE category II: medium risks - size(s): S/7-XXL/11

Manufacturer’s Information

according to Regulation (EU) 2016/425, Annex II, Section 1.4. (published in the Official Journal of the European Union)

Please read carefully before using! You are required to enclose this information leaflet when passing on the personal protective equipment (PPE), or to present it personally to the recipient. You may therefore reproduce this leaflet at your own discretion.

Declaration of Conformity

CE These gloves are classified as personal protective equipment (PPE). The CE mark confirms that the product satisfies the applicable requirements of Regulation (EU) 2016/425.

A. Markings on the gloves:

Trademark, art.-no. of manufacutrer, size, CE-icon, pictograms with the corresponding numbers of the relevant European PPE standards, i-mark, factory icon with date of manufacture: month/year, hourglass pictogramm with expiry date: month/year

teXXor — Brand label of manufacturer

2210 — Article no. of the manufacturer



Pictograms with the corresponding numbers of the relevant European PPE standards (example).

CE — The CE marking confirms compliance with the requirements of European Regulation 2016/425.



i mark: Reference to the manufacturer’s information.



Date of manufacture month/year: 00/0000



Expiry date month/year: 00/0000

B. Explanation and numbers of the standards whose requirements the gloves satisfy:

Standards retrieved from the Official Journal of the European Union. Available from DIN Media GmbH, D-10787 Berlin. www.dinmedia.de

EN ISO 21420:2020 - Protective gloves - General requirements and test methods

EN 388:2016+A1:2018 - Protective gloves against mechanical risks:

Protective gloves against mechanical risks must achieve at least Level 1 or Level A in at least one of the properties (abrasion, cut, tear and puncture resistance) of the TDM cut resistance test according to EN ISO 13997:1999.

Abrasion resistance:	The number of abrasion cycles required to rub through the test specimen.
Cut resistance (Coupe-Test):	The number of test cycles in which the test specimen is cut through with constant force and repeated contact.
Tear resistance:	The force needed to continue tearing the cut sample.
Puncture resistance:	The force needed to puncture the sample using a standardized test stylus.
Cut resistance (TDM):	The minimum force that is necessary to cut through the test specimen with a single contact.

EN 388:2016+A1:2018



2242B

Test criteria	Rating	Article 2210
A = Abrasion resistance	0 - 4	2
B = Cut resistance (Coupe test)	0 - 5	2
C = Tear resistance	0 - 4	4
D = Puncture resistance	0 - 4	2
E = Cut resistance (TDM) according to EN ISO 13997:1999	A - F	B
F = Impact protection test according to EN 13594:2015	P	X

Test	1	2	3	4	5
A = Abrasion resistance (number of abrasion cycles)	100	500	2000	8000	-
B = Cut resistance (index) Coupe test	1,2	2,5	5,0	10,0	20,0
C = Tear resistance (N)	10	25	50	75	-
D = Puncture resistance (N)	20	60	100	150	-

The higher the test number, the better the test performance. 0: indicates that the glove falls below minimum performance level for the given individual hazard. X: indicates that the glove has not been tested or the test method appears not to be suitable for the glove design or material. P means ‘passed’.

Test	A	B	C	D	E	F
E = Cut resistance according to EN ISO 13997:1999 (N)	2	5	10	15	22	30
Article 2210		7.8				

EN 13594:2015 - Impact protection:

Every area specified as providing protection against impact must be tested. The test method (dimensions of the test sample) does not permit impact testing of the finger protection. Products to protect against mechanical risks may be designed and manufactured in such a way that they offer specific impact damping (e.g. impact protection on the knuckles, the back of the hand, the palms). These articles must satisfy the requirements of Level 1 according to EN 13594:2015. Gloves do not offer impact protection.
The results of the Coupe test must only be taken as indications if blunting occurs during the cut resistance test (B), while the TDM cut resistance test (E) provides reference results in regard to performance.

WARNING:

The overall classification for products with two or more layers does not necessarily indicate the performance of the outermost layer. Gloves and forearm protectors with mechanical resistance that achieve and demonstrate Level 1 tear resistance (C) or higher must not be worn if there is a risk of them catching when operating machines with moving parts. For gloves, the tests refer to the palms.

EN 407:2020 - Protective gloves and other hand protective equipments against thermal risks (heat and/or fire)

EN 407:2020



X2XXXX

test criteria	Possible ratings	Article 2210
A = limited flame spread	0 - 4	X
B = contact heat	0 - 4	2
C = convective heat	0 - 4	X
D = Radiant heat	0 - 4	X
E = Small splashes of molten metal	0 - 4	X
F = Large quantities of molten metal	0 - 4	X

The letter 'X' in place of a number indicates that the glove is not intended for the purpose covered by this test.

Test	Test result according to EN407	1	2	3	4
Limited Flame Spread:	After Flame Time (s)	≤15	≤10	≤3	≤2
	After Glow Time (s)	-	≤120	≤25	≤5
Contact heat:	Contact temperature °C	100	250	350	500
	Threshold time (s)	≥15	≥15	≥15	≥15
Convective heat:	Heat transfer index HTI (s)	≥4	≥7	≥10	≥18
Radiant heat:	Heat transfer t24 (s)	≥7	≥20	≥50	≥95
Small splashes of molten metal:	Number of splashes	≥10	≥15	≥25	≥35
Large splashes of molten metal:	Molten iron (g)	30	60	120	200

WARNING:

The glove must not come into contact with an open flame if it has not been tested or achieved at least performance level 1 in the limited flame spread test.
The levels only apply to the entire products and all of its layers for articles comprising several separable layers.

EN 511:2006 - Protective gloves against cold:

This Pictogram indicates that the product protects against convective and conductive cold and complies under EN 511:2006.

EN 511:2006



X2X

Test criteria	Possible performance levels	Article 2210
Convective cold (table 1)	0 - 4	X
Contact cold (table 2)	0 - 4	2
Water penetration	0 - 1	X

Table 1 - Thermal insulation values:

Performance level	Thermal insulation ITR in m² K/W
1	0,10 ≤ ITR < 0,15
2	0,15 ≤ ITR < 0,22
3	0,22 ≤ ITR < 0,30
4	0,30 ≤ ITR

Table 2 - Thermal resistance values:

Performance level	Thermal resistance ITR in m² K/W
1	0,025 ≤ R < 0,050
2	0,050 ≤ R < 0,100
3	0,100 ≤ R < 0,150
4	0,150 ≤ R

The higher the test number, the higher the test performance. The code 'X' in place of a number indicates that the glove was not designed for applications covered by this test. Gloves in Levels 2 to 4 for convective cold and contact cold must achieve at least Level 2 for abrasion resistance and tear resistance according to EN 388:2016+A1:2018; the highest level for convective cold and contact cold must otherwise be given as Level 1.
The levels and their protective effects only apply to the complete assembly for gloves that consist of several parts.

WARNING:

This glove provides a protection for limited contact time with cold products.
Gloves that do not do not fulfil the criteria of Level 1 for waterproofing may lose their insulating properties when exposed to damp.



Tested on capacitive touchscreens. It is very important for the touchscreen function that the glove fits well on the hand. This functionality depends on the touchscreen sensitivity of the device. The touchscreen function of the device, if present, must be switched on and adjusted. As the gloves have conductive threads, they should not be used in areas where there is a risk of static electricity and electric shock. The performance of the touchscreen may vary due to temperature and humidity.

C. Purpose, applications and risk assessment:

Applicable for general assembly work with medium risks in cool environments, e.g. in the craft trade, construction sector, trade fair construction, automotive industry, mechanical engineering industry, agricultural sector

These products satisfy the requirements of the quoted standards. Please note that the actual conditions of use cannot be simulated and that the decision on the article suitability for its intended purpose therefore lies exclusively with the user. The manufacturer is not responsible for improper use. Hence, an assessment of the residual risk should be performed before use in order to determine whether this article is suitable for its intended purpose. Kindly note the printed pictograms and performance levels.

Kindly note the printed pictograms and performance levels.

Precautionary measures before use:

When donning the glove, please ensure that both glove and hand are clean, glove size is right, and it is properly fit on the contours and crotches of fingers. In case of contamination / perspiration, take off the glove, allow it to dry before wearing again and/or discard depending on the condition of glove.

When an indication of hand hygiene precedes a contact that also requires glove usage, hand rubbing or hand washing should be performed before donning glove.

Precautionary measures during use:

- **These products must never be immersed in chemical substances or come into contact with chemical substances.**
- Only use products with a printed chemical pictogram when handling chemicals.
- Make certain that the selected product is resistant to the chemicals being used.

- Do not use these products to protect against serrated edges or blades, etc.
- If products must be used in a hot environment, make certain that they satisfy the requirements of EN 407:2020 and that they were tested as specified therein.
- Do not use the products close to entanglements.
- Check the products carefully before use to make certain there are no defects or imperfections.
- Products meeting the requirement for resistance to puncture in accordance with EN 388:2016+A1:2018 may not be suitable for protection against sharply pointed objects such as hypodermic needles.
- Discard damaged, worn, dirty or soiled products, irrespective of the substance (including on the inside), as they may lead to skin irritation and rashes. Consult a doctor or dermatologist should such cases arise.
- For further information regarding the permissible user exposure, e.g. temperature, duration please contact the manufacturer.

Doffing instruction:

- Clean off the outside of the gloves at least daily and prior to removing them.
- Loosen the gloves on both hands. Hold hands down to prevent the material, product, or contaminated water from dripping onto your skin or clothing.
- Keep the gloves down and remove the first glove only to the fingers – the cuff will remain over your palm
- Grab the second glove with the first glove and remove it. The first glove should slip off.
- Handle gloves by the inside only – the area not contaminated. Avoid touching the outside of the glove.
- Wash your hands with soap and water – do not use hand sanitizers.

D. Cleaning, care and disinfecting:

Care instructions:



Do not wash and bleach the gloves. Drying in tumbler is not possible. Do not iron. Professional dry and wet cleaning is not allowed.

Both new and used gloves must be checked carefully for any damage before they are worn. Never store dirty gloves if they are intended for reuse. Users are advised to carefully remove the gloves on the right and then the left if it is not possible to remove the soiling or if doing so would present a danger. Here, use the hand wearing the glove in such a way that the other glove can be removed without coming into contact with the soiling.

E. Storage and ageing:

Keep in a cool, dry place; do not expose to direct sunlight; keep away from any ignition sources; store in the original packaging if possible. The mechanical properties of the products will not change for a period of up to 3 years from the manufacturing date, provided they are stored as recommended. A precise service life cannot be stated, as it depends on the type of use and on whether the user ensures that the products are used exclusively for their intended purpose. The manufacturing date (month/year) is stated on the products.

F. Disposal:

Used products may be contaminated with environmentally harmful or hazardous substances. Dispose them in accordance with applicable local laws.

G. Material composition:

Liner: acrylic / polyester
Coating: latex

H. Packaging:

This item will be delivered in a uniform cardboard box with a content of: 72 pair
The smallest sales unit is: 6 pair

I. Health risks:

This product may contain latex obtained from natural rubber that may provoke allergic reactions. You should nonetheless consult a doctor or dermatologist if you experience an allergic reaction.

Notified body responsible for the EU Type Examination:

CTC
Parc Scientifique Tony Garnier
4 rue Hermann Frenkel
69367 Lyon Cedex 07
France
Notified Body No.: 0075

Manufacturer’s name and address:

BIG Arbeitsschutz GmbH, Bundesstraße 17, 21244 Buchholz, Germany

For the full Declaration of Conformity and additional technical information, please visit:

www.big-arbeitsschutz.de

issued on 17.01.2025/Rev.05