PLANAM

jacket Weld Shield

Work jackets

Item number: 160-25-117; 160-25-118



PPE CATEGORY III

The front press studs are concealed beneath the cover.

Material	**84 % cotton, 15 % Polyester, 1 % carbon fibres (antistatic fibres); with antistatic and flame-retardant finish**
Fabric weight	**Outer fabric: approx. 365 g/m²**
Colours	
Sizes	**42, 44, 46, 48, 50, 52, 54, 56, 58, 60, 62, 64, 90, 94, 98, 102, 106, 110**
Sales unit	**Piece**
Manufacturer	**PLANAM-Arbeitsschutz Vertriebs-GmbH**

Protection and standards

EN ISO 11611:2015	Protective clothing for welding and allied processes · class 1 A1
EN ISO 11612:2015	Protective clothing against heat and flame · A1 B1 C1 E3 F1
EN 1149-5:2018	Electrostatic dissipative protective clothing
EN 1149-3:2004	Test method for charge decay
Marking	UV STANDARD 801 · UVS 096281

Care

Wash at 60 °C, normal process; Do not bleach; Dry at normal temperature; Iron at high temperature (3 dots); Do not dry clean; Maximum 10 wash cycles

Important information

EN ISO 11611: Welding and allied processes
EN ISO 11612: Heat and flame
EN 1149-5: Only as a closed suit within a suitable earthed system. The person's resistance to earth must be less than 10^8 Ω. No protection against electric shock.
EN 1149-3: Test method for charge decay in conjunction with EN 1149-5.
UV STANDARD 801: Applies to the material and colour version marked accordingly by the manufacturer.

Product overview based on manufacturer documents. Refer also to the original instructions and EU declaration of conformity.