PLANAM

bib trousers Major Pect

Bib trousers

Item number: 160-35-183



PPE CATEGORY III

Sewn-on buttons adjust the waistband width.

Material	**64 % cotton, 35 % Polyester, 1 % carbon fibres; 2/2 diagonal twill; antistatic, flame-retardant and fluorocarbon finished**
Fabric weight	**Outer fabric: approx. 370 g/m²**
Colour	
Sizes	**42, 44, 46, 48, 50, 52, 54, 56, 58, 60, 62, 64, 90, 94, 98, 102, 106, 110**
Sales unit	**Piece**
Manufacturer	**PLANAM-Arbeitsschutz Vertriebs-GmbH**

Protection and standards

EN ISO 11611:2015	Protective clothing for welding and allied processes · class 1 A1
EN ISO 11612:2015	Protective clothing against heat and flame · A1 B1 C1 E3 F1
EN 1149-5:2018	Electrostatic dissipative protective clothing
EN 13034:2005+A1:2009	Limited protection against liquid chemicals · Type 6; Abrasion class 6, Tear resistance class 2, Tensile strength class 5, Seam strength class 5, Puncture resistance class 2; 30% H2SO4 R3/P3; 10% NaOH R3/P3; o-xylene R2/P3; Butan-1-ol R2/P3
EN 61482-2:2020	Protection against the thermal hazards of an electric arc · APC 1
EN 1149-3:2004	Test method for charge decay
Marking	UV STANDARD 801 · UVS 064970

Care

Wash at 60 °C, normal process; Do not bleach; Dry at normal temperature; Iron at medium temperature; Do not dry clean; Maximum 5 wash cycles

Important information

Product overview based on manufacturer documents. Refer also to the original instructions and EU declaration of conformity.

Planam bib trousers Major Pect

Important information

EN ISO 11611: Welding and allied processes

EN ISO 11612: Heat and flame

EN 1149-5: Only as a closed suit within a suitable earthed system. The person's resistance to earth must be less than 10^8 Ω. No protection against electric shock.

EN 13034: Limited protection against small splashes of liquid chemicals; suit; Check protection against other chemicals separately

EN 61482-2: Thermal hazards of an electric arc

EN 1149-3: Test method for charge decay in conjunction with EN 1149-5.

UV STANDARD 801: Applies to the material and colour version marked accordingly by the manufacturer.