CANIS

CXS Gera gloves with PU coating Touch

Touchscreen-assembly gloves

Item number: 110-50-012



PPE CATEGORY II

Copper fibres at three fingertips enable touchscreen operation.

Material	**100 % Polyester** **Coating: polyurethane (PU)**
Colour	
Sizes	**7, 8, 9, 10**
Sales unit	**Pair**
Manufacturer	**CANIS SAFETY a.s.**

Performance levels to EN 388

Abrasion resistance	2 of 4
Cut resistance (Coupe)	1 of 5
Tear resistance	2 of 4
Puncture resistance	1 of 4
Cut resistance (TDM)	X - no rated level

EN ISO 21420	General requirements for protective gloves
EN 388	Mechanical risks · 2121X

Care

Wash synthetics at a maximum of 40 °C using a mild process; maximum 5 wash cycles. Rinse cold and spin briefly. Do not use biological detergents, optical brighteners or fabric softener. Do not bleach. Do not tumble dry. Do not iron. Do not dry clean. Alternatively remove dirt with a damp cloth or soft brush. Dry at room temperature away from heat sources. Replace worn, burnt, heavily soiled or hardened gloves.

Product overview based on manufacturer documents. Refer also to the original instructions and EU declaration of conformity.