CXS Delmenhorst assembly gloves with latex coating

Latex assembly gloves

Item number: 110-50-019



PPE CATEGORY II

The crinkle latex finish on the palm and fingers is designed for improved grip.

Material	**Outer material: 100 % Polyester** **Coating: Latex**
Colour	
Sizes	**7, 8, 9, 10, 11, 12**
Country of origin	**China**
Sales unit	**Pair**
Manufacturer	**CANIS SAFETY a.s.**

Performance levels to EN 388

Abrasion resistance	**2 of 4**
Cut resistance (Coupe)	**1 of 5**
Tear resistance	**3 of 4**
Puncture resistance	**1 of 4**
Cut resistance (TDM)	**X - no rated level**

EN ISO 21420	General requirements for protective gloves
EN 388	Mechanical risks · 2131X
EN 407	Thermal risks (heat and/or fire) · X1XXXX

Care

Do not wash. Do not bleach. Do not tumble dry. Do not iron. Do not dry clean. Remove dirt with a soft brush; Wipe the coating with a damp cloth if necessary. Dry damp gloves at room temperature away from heat sources. Replace worn, burnt, heavily soiled or hardened gloves.

Product overview based on manufacturer documents. Refer also to the original instructions and EU declaration of conformity.