FRISTADS

Flamestat Green high-visibility

Winter jackets

Item number: 220-25-025



PPE CATEGORY III

The Flamestat Green winter jacket has quilted padding and ripstop reinforcements.

Material	**Outer material: 50 % modacrylic, 22 % Lyocell, 16 % polyamide, 5 % cotton, 4 % organic cotton, 2 % elastane, 1 % antistatic fibres** **Padding: 100 % Polyester** **Lining: 40 % modacrylic, 37 % flame-retardant viscose, 22 % viscose, 1 % antistatic fibres**
Colour	
Sizes	**XS, S, M, L, XL, XXL, 3XL, 4XL, 5XL, 6XL**
Country of origin	**Ukraine**
Weight	**1.9 kg per item**
Fabric weight	**Outer material 330 g/m², Ripstop 335 g/m²** **Padding 170 g/m², Sleeves 120 g/m²** **Lining 195 g/m²**
Sales unit	**Piece**
Manufacturer	**Fristads AB**

Protection and standards

EN ISO 13688:2013+A1:2021	General requirements for protective clothing
EN 1149-5:2018	Electrostatic dissipative protective clothing · electrostatic protective properties; no ESD verification
EN ISO 20471:2013+A1:2016	High-visibility clothing · class 3
EN 342:2017	Protective clothing against cold · Thermal insulation value 0,360 m²K/W(B) only together with trousers 109424
EN ISO 11612:2015	Protective clothing against heat and flame · A1 A2 B1 C1 E2 F1
EN 61482-2:2020	Protection against the thermal hazards of an electric arc

Product overview based on manufacturer documents. Refer also to the original instructions and EU declaration of conformity.

Fristads Flamestat Green high-visibility winter jacket

Protection and standards

EN ISO 11611:2015	Protective clothing for welding and allied processes · class 1
EN 13034:2005+A1:2009	Limited protection against liquid chemicals · Type PB[6] (partial body protection)
EN 13758-2:2003+A1:2006	UV protective properties of clothing · UPF 40+
Marking	Electric arc test · APC 2, ELIM 27 cal/cm², ATPV 28 cal/cm² (individual model; full body protection only with compatible clothing in accordance with the manufacturer's instructions)
OEKO-TEX® STANDARD 100	
Marking	Certificate number: Ö 97-055
OEKO-TEX®	Product class II

Care

Wash at a maximum of 60 °C, normal process. Do not bleach. Tumble dry at low temperature (maximum 60 °C). Iron at a maximum of 160 °C. Do not dry clean.

Product overview based on manufacturer documents. Refer also to the original instructions and EU declaration of conformity.