FRISTADS

Flamestat Green high-visibility stretch trousers 2956 GFS

Waist trousers

Item number: 220-35-002



PPE CATEGORY III

The reflective prints are arranged in segments.

Material	**Main material and ripstop stretch panels: 50 % modacrylic, 22 % Lyocell, 16 % polyamide, 5 % cotton, 4 % organic cotton, 2 % elastane, 1 % antistatic fibres Reinforcements: 80 % Aramid, 18 % polyurethane, 2 % antistatic fibres**
Colour	
Sizes	**44, 46, 48, 50, 52, 54, 56, 58, 60, 62, 64, 66**
Country of origin	**Ukraine**
Weight	**1.1 kg per item**
Fabric weight	**330 g/m²** **Ripstop 335 g/m²**
Sales unit	**Piece**
Manufacturer	**Fristads AB**

Protection and standards

EN ISO 13688:2013+A1:2021	General requirements for protective clothing
EN 1149-5:2018	Electrostatic dissipative protective clothing · electrostatic protective properties; no ESD verification
EN ISO 20471:2013+A1:2016	High-visibility clothing · class 2
EN ISO 11612:2015	Protective clothing against heat and flame · A1 A2 B1 C1 E2 F1
EN 61482-2:2020	Protection against the thermal hazards of an electric arc
EN ISO 11611:2015	Protective clothing for welding and allied processes · class 1
EN 13034:2005+A1:2009	Limited protection against liquid chemicals · Type PB[6] (partial body protection)

Product overview based on manufacturer documents. Refer also to the original instructions and EU declaration of conformity.

Fristads Flamestat Green high-visibility stretch trousers 2956 GFS

Protection and standards

EN 13758-2:2003+A1:2006	UV protective properties of clothing · UPF 40+
EN 14404:2004+A1:2010	Knee protection for work in a kneeling position · Type 2, Performance level 1; only as an approved combination with kneepads 124292 and the kneepad pocket approved by the manufacturer
Marking	Electric arc test · APC 1, ELIM 13 cal/cm², EBT 15 cal/cm² (individual model; full body protection only with compatible clothing in accordance with the manufacturer's instructions)
OEKO-TEX® STANDARD 100	
Marking	Certificate number: Ö 97-055
OEKO-TEX®	Product class II

Care

Wash at a maximum of 60 °C, normal process. Do not bleach. Tumble dry at low temperature (maximum 60 °C). Iron at a maximum of 160 °C. Do not dry clean.

Product overview based on manufacturer documents. Refer also to the original instructions and EU declaration of conformity.