Flamestat high-visibility stretch trousers 2162 ATHF

Waist trousers

Item number: 220-35-005



PPE CATEGORY III

A loop is provided for an ID holder.

Material	**Main material: 45 % modacrylic, 34 % cotton, 17 % polyamide, 2 % elastane, 2 % antistatic fibres** **Reinforcements: 45 % modacrylic, 35 % cotton, 18 % polyamide, 2 % antistatic fibres**
Colour	
Sizes	**44, 46, 48, 50, 52, 54, 56, 58, 60, 62, 64, 66**
Country of origin	**Madagascar**
Fabric weight	**Stretch 265 g/m²** **Reinforcement 300 g/m²**
Sales unit	**Piece**
Manufacturer	**Fristads AB**

Protection and standards

EN ISO 13688:2013+A1:2021	General requirements for protective clothing
EN 1149-5:2018	Electrostatic dissipative protective clothing · electrostatic protective properties; no ESD verification
EN ISO 20471:2013+A1:2016	High-visibility clothing · class 1
EN ISO 11612:2015	Protective clothing against heat and flame · A1 B1 C1 F1
IEC 61482-2:2018	Protection against the thermal hazards of an electric arc
EN ISO 11611:2015	Protective clothing for welding and allied processes · class 1
EN 13034:2005+A1:2009	Limited protection against liquid chemicals · Type PB[6] (partial body protection)
EN 14404:2004+A1:2010	Knee protection for work in a kneeling position · Type 2, Performance level 1; only as an approved combination with kneepads 124292 or 127440 and the kneepad pocket approved by the manufacturer

Product overview based on manufacturer documents. Refer also to the original instructions and EU declaration of conformity.

Fristads Flamestat high-visibility stretch trousers 2162 ATHF

Protection and standards

EN 14404-3:2024	Knee protection system comprising kneepads and garment · Type 2, Performance level 1; only as an approved combination with kneepads 132082 and the kneepad pocket approved by the manufacturer KP2b
Marking	Electric arc test · APC 1, ELIM 8 cal/cm² (individual model; full body protection only with compatible clothing in accordance with the manufacturer's instructions)
OEKO-TEX® STANDARD 100	
Marking	Certificate number: SE 23-311
OEKO-TEX®	Product class II

Care

Wash at a maximum of 60 °C, normal process. Do not bleach. Tumble dry at low temperature (maximum 60 °C). Iron at a maximum of 160 °C. Do not dry clean.

Product overview based on manufacturer documents. Refer also to the original instructions and EU declaration of conformity.